



PRODUCT INFORMATION Error! Bookmark not defined.

PRODUCT: 10-MINUTE FLUSH

PART NO.: C1412C

FUNCTION AND APPLICATION: Used as a fast-acting radiator flush to remove scale, scum and rust from cooling systems when changing coolant or as a periodic cleaner. Safe for aluminum radiators.

OUTSTANDING PROPERTIES: Does not require a neutralizer. Contains no acids. Cleans scum, rust and scale deposits from cooling system in ten minutes.

USE DIRECTIONS: Drain cooling system. Save anti-freeze for reuse after rinsing. NOTE: Used anti-freeze/coolant and radiator fluids may be considered hazardous in some areas. Flush with water to remove all traces of engine coolant. Pour entire contents of container into radiator and refill with water. Put radiator cap back on, loosely. Run engine 10 minutes and drain system. Flush until water is clean. Refill cooling system. Use caution when removing radiator cap while system is hot.

LIMITATIONS: Will not flush out severe accumulations of deposits and rust. Adequate for most applications. For severely clogged systems consult a professional radiator repair shop.

PRECAUTIONS: View MSDS at www.gunk.ca

DISPOSAL: Safeguard our environment. Use and dispose of product, residue and used anti-freeze/coolant and radiator fluids in accordance with all local, provincial and federal laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto ground or into storm sewer systems.

PACKAGING: 350mL plastic bottle with c/r closure, packed 12 per case.

U.P.C. CODE: 0-60959-31401-6

WEIGHT PER CASE: 11 lbs. 5 kg

CASE SIZE: 11 ½ x 8 ½ x 6 ½