



PRODUCT INFORMATION

PRODUCT: RADIATOR REPAIR

PART NO.: C501C, C501V

FUNCTION & APPLICATION: Stops leaks in radiators instantly and prevents new leaks from developing. Works in both water and anti-freeze solutions. Drain and flush system before using. Contains rust inhibitor. Will not harm metal, rubber hoses, gaskets, or any part of the cooling system when used as directed. For use on car, tractor, or small trucks.

OUTSTANDING PROPERTIES: Works in both water and anti-freeze solutions. Although sold as a temporary repair, often seals leaks permanently. Will prevent new leaks from developing. Safe for Aluminum Radiators.

USE DIRECTIONS: **Caution: Never remove pressure cap from a hot engine. Burns may result from contents spewing over and causing injury.** With heater on, flush cooling system thoroughly with Solder Seal Gunk 10 Minute Flush C1412C. Fill radiator with 50/50 coolant/water mixture, leaving enough space to add Stop Leak. Start engine and turn heater on. Gradually pour entire contents (28.3g) into radiator only. Circulation of the water will do the rest. Run engine for 10 minutes or until leak has stopped.

PRODUCT LIMITATIONS: Will not stop major leaks or solve major mechanical problems.

PRECAUTIONS: View MSDS at www.gunk.ca

STORAGE & HANDLING: Store in a cool, dry place, away from oxidizers. The wearing of contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial, and local laws and regulations.

PACKAGING: C501C - 28.3 g Tube, packed 12 per dispenser, 6 dispensers per case.
C501V - 28.3 g Tube, packed on display card, 10 cards per case.

U.P.C. CODE: C501C - 0-60959-00553-2 C501V - 0-60959-35012-0

WEIGHT PER CASE: C501C - 6 lbs. 2.72 kg C501V - 1.5 lbs .68 kg

CASE SIZE: C501C - 9 x 9 x 10. C501V - 6 x 7 x 5.