



PRODUCT INFORMATION

PRODUCT: TRANSEAL

PART NO.: M1512C

FUNCTION AND APPLICATION: This product is added to automatic transmissions to swell seals and provide additional high-pressure lubrication. This product should aid in stopping transmission leaks, noise and minimize wear.

OUTSTANDING PROPERTIES: TRANSEAL is designed to swell seals and provide additional high-pressure lubrication. TRANSEAL will stop minor transmission leaks for sufficient time to obtain proper repairs. TRANSEAL reduces gear and bearing noise, making shifting quieter, faster and smoother. TRANSEAL is non-corrosive, non-clogging and non-foaming.

USE DIRECTIONS: Add one bottle to automatic transmissions. Leaks should stop within 160 km of normal driving. If leak persists, replacement of seals is indicated. For preventive maintenance, add one bottle each 16,000 km. Do not overfill transmission. Add one bottle each time transmission fluid is changed.

PRODUCT LIMITATIONS: Will not correct cracked, broken or excessively worn seals or repair worn transmissions.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: 350-ml bottle with c/r cap, packed 12 per case.

U.P.C. CODE: 0-60959-13151-4

WEIGHT PER CASE: 10 lbs. 4.54 kg

CASE SIZE: 10 x 7 x 9