



PRODUCT INFORMATION

PRODUCT: BEARIN' SEAL

PART NO.: M1616C

FUNCTION AND APPLICATION: Stops minor oil leaks in front and rear main bearing seals, head gaskets and timing chain covers. Will not harm engine parts. Starts sealing action immediately.

OUTSTANDING PROPERTIES: Functions by impregnating and swelling gasket material which will in turn, stop minor leaks created by wear and overheating. Mixes well with all regular and synthetic motor oils.

USE DIRECTIONS: For best results, use immediately following oil and filter change. Start engine and warm to operating temperature. Add contents of container to oil and drive for 15 minutes. Leaks should stop within 48 hours. Continued leakage may indicate excessively worn parts, which may require mechanical replacement.

PRODUCT LIMITATIONS: Not intended as a repair for excessively worn parts and broken or cracked seals.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Do not wear contact lenses. Keep away from ignition sources. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: 350-ml bottle with c/r cap, packed 12 per case.

U.P.C. CODE: 0-60959-13161-3

WEIGHT PER CASE: 11 lbs. 5 kg

CASE SIZE: 10 x 9 x 7