



PRODUCT INFORMATION

PRODUCT: INSTANT STARTING FLUID

PART NO.: M3512C

FUNCTION AND APPLICATION: To promote quick starting of gasoline and diesel engines under extreme cold conditions.

OUTSTANDING PROPERTIES: Produce quick, smooth starting of gasoline and diesel engines under extreme cold conditions down to -53°C. Contains at least 45% of Diethyl Ether. Saves battery and ignition during cold weather. Contains upper cylinder lubricant and corrosion inhibitors.

USE DIRECTIONS: Spray fluid directly into air cleaner of air intake before starting engine. Avoid spraying for over 5 seconds per attempt. If engine still refuses to start repeat procedure up to 3 times. If engine still does not start, ignition repairs may be indicated. ALWAYS AVOID SPRAYING WHILE IGNITION IS ON TO AVOID POSSIBILITY OF EXPLOSION OR FIRE.

PRODUCT LIMITATIONS: Do not use with engines, which use glow plugs (especially diesel passenger autos). Avoid spraying while turning engine simultaneously. Avoid overuse of product when engine fails to start with recommended procedure. Engine damage or personal injury may result. Avoid flooding engine before using.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 50°C. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Use with adequate ventilation. Avoid using in low lying or confined areas. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: 210g aerosol tin, packed 12 per case.

U.P.C. CODE: 0-60959-02578-3

WEIGHT PER CASE: 9 lbs. 4.09 kg

CASE SIZE: 11 x 8 x 7