



## PRODUCT INFORMATION

PRODUCT: GUNK MOTOR FLUSH

PART NO.: MF2C

FUNCTION AND APPLICATION: A blend of sludge dissolving solvents which can be added to an engine a few minutes before an oil change to flush out deposits and free valves and rings.

OUTSTANDING PROPERTIES: Frees up sludge associated with slow city driving. Can be easily used by car owners or professional technicians just before oil changes. Works in all gas or diesel engines.

USE DIRECTIONS: 1. Check that engine oil is at a safe operating level. 2. Add MF to cold engine before changing oil and filter. Idle-engine at normal speed for 5 minutes. GUNK® Motor Flush will circulate throughout the entire lubricating system of your engine removing sludge, gums and varnishes from engine and oil pan. It also frees sticking valves and rings. DO NOT DRIVE CAR. DO NOT REV ENGINE. 3. Drain oil and remove oil filter. 4. Replace filter and drain plug and refill engine with new oil. NOTE: On engines with high mileage or excessive deposits remove and clean the oil pan. IMPORTANT: Use entire contents of container after opening. Do not store partially used container.

PRECAUTIONS: View MSDS at [www.gunk.ca](http://www.gunk.ca).

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Keep away from heat and flame. Product spilled on hot surfaces may ignite. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: MF2C - 946ml plastic bottles with child resistant cap.

U.P.C. CODE: MF2C - 0-60959-13061-6

WEIGHT PER CASE: MF2C - 24 lbs. 10.9 kg

CASE SIZE: MF2C - 16 X 9 X 9