



PRODUCT INFORMATION

PRODUCT: HOLD-ZIT STRAPS

PART NO.: R79BC, R715BC, R722BC, R731BC, R741BC,

FUNCTION AND APPLICATION: Hundreds of uses . . . tarpaulins, trunk lids, luggage racks, ladders, boat moorings, etc.

TECHNICAL SPECIFICATIONS: Laboratory tested in accordance with ASTM D-2000 specification, and the respective suffix standard.

: Tensile strength: 1800 PSI, ASTM D-412 STD.

: Elongation: 600% ASTM D-412 STD.

: Cold Temp. Flexibility: -40C ASTM D-476 STD.

Hold-Zit compound is an EPDM (Ethylene Propylene Diene Monomer) rubber. It is used in preference to SBR (Styrene Butadiene Rubber) because of excellent flexibility at low temperatures and resistance to ozone and aging.

PRODUCT LIMITATIONS: The maximum safe stretch is 1 1/2 times the relaxed length, i.e. R722BC is 22 inches long and should not be stretched over 33 inches.

PRECAUTIONS: Sudden rupture or disconnect from anchor while in a stretched position can cause serious injuries. Wear safety glasses during tie down and disconnect. Not to be substituted as a primary tie down device for load. Inspect strap before each use. Discard if cut, cracked or abraded.

PACKAGING: R79BC, R715BC, R722BC, R731BC and R741BC packed 50 per case.

U.P.C. CODE: R79BC 0-60959-01783-2 R715BC 0-60959-01775-7
R722BC 0-60959-01777-1 R731BC 0-60959-01779-5 R741BC 0-60959-017818

WEIGHT PER CASE: R79BC-10 lbs. 4.54 kg R715BC-14 lbs. 6.36 kg
R722BC-17 lbs. 7.7 kg R731BC-19 lbs. 8.63 kg
R741BC-25 lbs. 11.3 kg

CASE SIZE: R79BC-10X8X6 R715BC-18X8X6 R722BC-23X8X5
R731BC-21X13X6 R741BC-21X13X6