

**PRODUCT: SUPER CONCENTRATE** 

PART NO.: SC3, SC5, SC8

FUNCTION AND APPLICATION: Degreaser for engines, machinery, metal parts, floors.

<u>OUTSTANDING PROPERTIES:</u> A Super Concentrated liquid soap which must be diluted with no less than 5 parts of only aliphatic type petroleum distillate such as kerosene, light fuel oil, Stoddard Solvent, mineral spirits, etc. WARNING: NEVER USE EXPLOSIVE GASOLINE! - OR AROMATIC TYPE SOLVENTS.

<u>USE DIRECTIONS:</u> *MIXING INSTRUCTIONS*: Use container that is completely free of water. Average degreasing requires one part of S-C to nine parts of solvent. *HOW TO USE* - Apply generously only to moisture-free surfaces by spray or brush, or submerge parts in soak-tank filled with S-C solution. Allow sufficient time for penetration of grease, and when necessary brush S-C solution into extremely heavy deposits. To complete the cleaning process ALL SURFACES MUST BE RINSED THOROUGHLY WITH A STRONG STREAM OF WATER. Rinse overspray from exterior body surfaces immediately to prevent the possibility of streaking or dewaxing. *ENGINE CLEANING TIPS* - Engine must be off and cool. Cover distributor, electronic components, carburetor and air intake systems as necessary. NOTE: Care must be taken with all under hood electronic components. Minimize rinse water, which can cause performance problems. Exposed electrical conductors (cracked or frayed wires or EC unit) can short circuit. Apply or spray generously on dry engine. Wipe any overspray from exterior body surfaces with a wet cloth at once to avoid dewaxing or streaking paint. Allow S-C to soak for about 5 minutes. Brush unusually heavy deposits. Rinse with fine stream of water from top down. When complete remove all covers and replace any removed parts. Start engine immediately and idle 15 minutes to assure complete drying of engine.

<u>PRODUCT LIMITATIONS:</u> The accidental addition of moisture, (even a few drops) to a GUNK S-C solution will drastically reduce its cleaning efficiency.

<u>WARNING:</u> DO NOT USE ON PLASTIC SURFACES WITHOUT PRE-TESTING. Do not use in septic systems. Do not use on asphalt.

<u>PRECAUTIONS</u>: Caution: Combustible. Eye and skin irritant. Harmful or fatal if swallowed. Vapors harmful. In case of eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If swallowed, DO NOT INDUCE VOMITING! DO NOT ADMINISTER ADRENALINE OR EPINEPHRINE! Get medical attention immediately! If inhaled, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance.

<u>STORAGE & HANDLING:</u> Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Use with adequate ventilation. Wear safety goggles or facemask. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

<u>DISPOSAL:</u> Safeguard our environment. Dispose of container, residue and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: SC3 - 3.78L can, 4 per case. SC5 18.92L pail. SC8 - 205L drum.

<u>U.P.C. CODE</u>: SC3 - 0-60959-19033-7 SC5 - 0-60959-02093-1 SC8 - 0 -60959-02095-5

WEIGHT PER CASE: SC3 33 lbs. 15 kg SC5 - 44 lbs. 20 kg SC8 - 398 lbs.176.8 kg

CASE SIZE: SC3 - 14 x 9 x 11 SC5 - 12 x 12 x 13 SC8 - 23 x 23 x 35

